

Welding Twin Hose (Oxygen / Acetylene)

Tube	:	SBR blended, black, smooth
Reinforcement	:	textile braided high tensile synthetic yarn
Cover	:	SBR blended, red/green/blue, smooth/corrugated, weather and ozone resistant
Temperature	:	- 40°C ~ + 90°C
Application	:	for Oxy-Acetylene gas welding
Color available	:	Red/Green or Red/Blue

I/ Welding Twin Hose without fitting

Normal size			Pressure		Standard length	Net weight	Measure-ment	
size	I.D.	O.D.	No. of	W.P.				B.P.
inch	mm		ply	PSI		M/roll	kg/roll	m ³ /roll
3/16	5	11.5	1	300	900	100	28	0.048
1/4	6	12.5	1	300	900	100	30	0.055
5/16	8	15.5	1	300	900	100	44	0.065
3/8	9.5	17.5	1	300	900	100	56	0.080



II/ Welding Twin Hose with B+B (9/16"-18) Brass fitting

Normal size			Pressure		Standard length	Net weight	Measure-ment	
size	I.D.	O.D.	No. of	W.P.				B.P.
inch	mm		ply	PSI		M/roll	kg/roll	m ³ /roll
1/4	6	12.5	1	300	900	15	4.5	0.010
1/4	6	12.5	1	300	900	30	9.0	0.020
5/16	8	15.5	1	300	900	15	6.6	0.012
5/16	8	15.5	1	300	900	30	13.2	0.024



GRACEDUTY COMPANY LIMITED

Room 1102 - 1104, 11/F., CRE Centre,
889 Cheung Sha Wan Road, Kowloon, Hong Kong, China

Tel: (852) 2420-5808 (6 Lines) Fax: (852) 2420-5507

E-mail : welding@graceduty.com.hk

<http://www.graceduty.com.hk>