

Air Carbon Arc Gouging Torch GD-5 (Type A, B, C & D)

Type A



Technical Specifications:

- Straight Handle with meter cable (2 Meter or 3 Meter)
- 360° Swivel cable end
- With Air Powered Valve
- Electrode size : 3/16"~3/8" Round (5.0mm~10.0mm)
3/16x15/32"~3/16x25/32" Flat (5x12mm~5x20mm)
- Work current : 800 Amps
- Air pressure : 80 P.S.I.
- Flow rate : 21 CFM
- Weight : 2.4 KG

Type B



Technical Specifications:

- Straight Handle with meter cable (2 Meter or 3 Meter)
- 360° Swivel cable end
- With Air Powered Valve
- Electrode size : 3/16"~3/8" Round (5.0mm~10.0mm)
3/16x15/32"~3/16x25/32" Flat (5x12mm~5x20mm)
- Work current : 800 Amps
- Air pressure : 80 P.S.I.
- Flow rate : 31 CFM
- Weight : 2.8 KG

Type C



Technical Specifications:

- Straight Handle with meter cable (2 Meter or 3 Meter)
- 360° Swivel cable end
- With Air Powered Valve
- Electrode size : 3/16"~15/32" Round (5.0mm~12.0mm)
3/16x15/32"~3/16x63/64" Flat (5x12mm~5x25mm)
- Work current : 1000 Amps
- Air pressure : 80 P.S.I.
- Flow rate : 31 CFM
- Weight : 2.6 KG

Type D



Technical Specifications:

- Straight Handle with meter cable (2 Meter or 3 Meter)
- 360° Swivel cable end
- With Air Powered Valve
- Electrode size : 3/16"~33/64" Round (5.0mm~13.0mm)
3/16x15/32"~3/16x63/64" Flat (5x12mm~5x25mm)
- Work current : 1500 Amps
- Air pressure : 80 P.S.I.
- Flow rate : 31 CFM
- Weight : 2.8 KG

GRACEDUTY COMPANY LIMITED

Room 1102 - 1104, 11/F., CRE Centre,
889 Cheung Sha Wan Road, Kowloon, Hong Kong, China
Tel: (852) 2420-5808 (6 Lines) Fax: (852) 2420-5507
E-mail : welding@graceduty.com.hk <http://www.graceduty.com.hk>

rev.071219