

Straight Line Cutting Machine







HK-12 (II) Double Torch

HK-12

- ▶ Main body is made of aluminum die-casting.
- ► Mechanical non-stage Speed Adjustment with a knob.
- ► Advanced motor with fan for cooling, operate continuously under high temperature.
- ► Circle Rail or Circle Cutting Arm can be equipped for circular piece cutting (optional).
- ► Cutting edge shape : I. Y. V (45°).
- ▶ Applied to shipbuilding, oil field, metallurgical and other metal structure industry.

Accessories:

Straight Rail:		1.8meter (2 pcs)						
Cabtyre Cord assembl	y:	1 set						
Cutting Tip:		102 (for acetylene) or 106 (for	propa	ne) #	ŧ0,1,	2 - 1	рс е	ach
Weight:		1 pc (two torch set only)						
Weight supporter:		1 pc (two torch set only)						
Hexagon Bolt :		1 pc (two torch set only)						

Model No.	Overall Dimension	Supply	Cutting	Cutting	Dia. Of Circle	Motor	Weight
	(mm)	Voltage	Thickness	Speed	Cutting	(rpm)	(KG)
		V/HZ	(mm)	(mm/Min)	(mm)		
HK-12(I)	350 x 140 x 175	AC220/50	6-100	150-800	Ø290 - Ø540	1500	10
HK-12(II)	350 x 140 x 175	AC220/50	6-100	150-800	Ø290 - Ø540	1500	16

Graceduty Company Limited

Room 1102 - 1104, 11/F., CRE Centre, 889 Cheung Sha Wan Road, Kowloon, Hong Kong, China Tel: (852) 2420-5808 (6 Lines) Fax: (852) 2420-5507 E-mail: welding@graceduty.com.hk http://www.graceduty.com.hk