

Welding Blanket

Coated Fiberglass Welding Blanket



Features :

- Specialized plain weave fibreglass fabric featuring a unique coating. E.g. : Acrylic / Neoprene / Vermiculite.
- Coating is fire-retardant, and the powerful fabric is incombustible.
- Designed for slag / spark resistance, and resistant to incidental flame from cutting torches.
- Used to protect equipment and personnel that are both in the area of operation.

| | |
|---------------------|---|
| Material | 16 oz & 24 oz Fibreglass |
| Size | 6' x 6', 6' x 8', 10' x 10', or as per Customer requirement |
| Coating & Color | Acrylic / Neoprene (Gold Yellow), Vermiculite (Black) |
| Working Temperature | Up to 1000 °F for Neoprene, 1290 °F for Vermiculite |
| Brass Grommets | Yes <on all 4 sides, one grommet for each ~18"> |

Carbonized Fiber Welding Blanket (Velvet Cover)



Features :

- Lightweight, Soft & Flexible.
- Non-Flammable.
- Provides protection from sparks and spatter.

| | |
|---------------------|--|
| Material | 16 oz & 24 oz Carbonized Fiber |
| Size | 18" x 18", 6' x 8', 6' x 30M, or as per Customer requirement |
| Color | Black |
| Working Temperature | Up to 1800 ° F |
| Brass Grommets | No |

GRACEDUTY COMPANY LIMITED

Room 1102 - 1104, 11/F., CRE Centre,
889 Cheung Sha Wan Road, Kowloon, Hong Kong, China
Tel: (852) 2420-5808 (6 Lines) Fax: (852) 2420-5507
E-mail : welding@graceduty.com.hk <http://www.graceduty.com.hk>

rev.031020